



## **Zoning Resolution**

**THE CITY OF NEW YORK**  
**Zohran K. Mamdani, Mayor**

**CITY PLANNING COMMISSION**  
**Sideya Sherman, Chair**

# **43-31 - Other Special Provisions for Rear Yards**

File generated by <https://zr.planning.nyc.gov> on 4/9/2026

---

## 43-31 - Other Special Provisions for Rear Yards

---

LAST AMENDED

12/15/1961

M1 M2 M3

In all districts, as indicated, the #rear yard# requirements set forth in Section [43-26](#) (Minimum Required Rear Yards) shall be modified as set forth in this Section.

---

## 43-311 - Within 100 feet of corners

---

LAST AMENDED

12/15/1961

M1 M2 M3

In all districts, as indicated, no #rear yard# shall be required within 100 feet of the point of intersection of two #street lines# intersecting at an angle of 135 degrees or less.

---

## 43-312 - Along short dimension of block

---

LAST AMENDED

12/5/2024

M1 M2 M3

In all districts, as indicated, whenever a #front lot line# of a #zoning lot# coincides with the #short dimension of a block#, no #rear yard# shall be required within 100 feet of such #front lot line#.

---

### **43-313 - For zoning lots with multiple rear lot lines**

---

LAST AMENDED


4/30/2008



M1 M2 M3

In all districts, as indicated, for #zoning lots# with multiple #rear lot lines#, if a #rear yard# extends from a #rear lot line# away from the #street line# which is used to determine such #rear lot line#, the following rules shall apply:

- (a) A #rear yard# with a minimum depth of 20 feet shall be provided where such #rear lot line# coincides with a #rear lot line# of an adjoining #zoning lot#.





-  Rear Yard extending away from Street A
-  Rear Yard extending away from Street B

(33-303c, 43-313c)